## NSN 5930-01-167-5969

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-167-5969 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.875 inches **Body Length:** 1.090 inches **Body Width:** 0.400 inches **Body Height:** 0.620 inches **Unthreaded Mounting Hole Diameter:** 0.114 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.406 inches **Actuator Style:** Leaf **Actuator Width:** 0.154 inches **Actuator Free Position Height:** 0.600 inches **Maximum Voltage Rating In Volts:** 250.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 4.0 grams **Switch Actuating Force:** 20.0 grams **Actuator Movement:** 0.281 pretravel inches and 0.093 overtravel inches and 0.070 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 250.000 milliamperes resistive dc and 10.000 amperes resistive ac **Terminal Type And Quantity:** 3 quick disconnect, male Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## **NSN 5930-01-167-5969** Sensitive Switch - Page 2 of 2



Fiig:

A053a0