NSN 5930-01-167-6902

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-167-6902

| Thread Class: |
|---|
| 2a single mounting facility |
| Thread Length: |
| 0.375 inches single mounting facility |
| Overall Length: |
| 1.193 inches |
| Overall Height: |
| 1.484 inches |
| Overall Width: |
| 1.438 inches |
| Shaft Diameter: |
| 0.250 inches single actuator |
| Shaft Length: |
| 0.688 inches single actuator |
| Individual Section Quantity: |
| 1 |
| Switch Contact Basic Design: |
| Nonpile-up nonsymmetrical |
| Mounting Method: |
| Threaded bushing single mounting facility |
| Thready Qty Per Inch (tpi): |
| 32 single mounting facility |
| Thread Size: |
| 0.375 inches single mounting facility |
| Contact Voltage Rating In Volts: |
| 28.0 dc at sea level |
| Switch Actuator Indexing Position Quantity: |
| 9 single actuator |
| Shaft Type: |
| Round single actuator |
| Terminal Type: |
| Tab, solder lug |
| Contact Switching Action: |
| Makes before breaks single section rear |
| Switch Actuator Positioning Increment: |
| 30.0 degrees single actuator |
| Switch Actuator Stop Device Type: |
| Fixed stop single actuator |
| Contact Load Current Rating: |

Special Features:

1.5 amperes resistive load dc at sea level

Special circuit; nineactive contacts all open in full ccw position and progressively picked up and shorted to common contact with cw rotation; includes three blind terminals

NSN 5930-01-167-6902

Rotary Switch - Page 2 of 2



| Precious Material And Location: |
|--|
| Contact surfaces silver |
| Precious Material: |
| Silver |
| Style Designator: |
| Circular wafer, bushing mount |
| Thread Series Designator: |
| Unef single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A052b0