

View Online at <https://aerobasegroup.com/nsn/5930-01-168-0777>

Thread Class:

2a 1st mounting facility

Thread Length:

0.375 inches 1st mounting facility

Width Between Flats:

0.188 inches single actuator

Overall Length:

3.875 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.437 inches single actuator

Overall Diameter:

1.750 inches

Unthreaded Mounting Hole Diameter:

0.164 inches 2nd mounting facility

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

0.812 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing 1st mounting facility

Thread Size:

0.375 inches 1st mounting facility

Contact Voltage Rating In Volts:

300.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, parallel flatted single actuator

Terminal Type:

Tab, solder lug and wire lead

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load highest dc voltage rating at sea level and 50.0 milliamperes inductive load highest dc voltage rating at sea level

Special Features:

Solenoid actuated

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0