NSN 5930-01-168-2737

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-168-2737

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

0.540 inches

Overall Height:

1.695 inches

Overall Width:

1.700 inches

Distance Between Mounting Facility Centers:

1.437 inches single mounting facility

Individual Section Quantity:

1

Mounting Method:

Flange single mounting facility and threaded hole single mounting facility

Actuator Type:

Double push button all actuators

Features Provided:

Illuminated

Thready Qty Per Inch (tpi):

56 single mounting facility

Thread Size:

0.086 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

10 all actuators

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 single section

Contact Arrangement Truth Table:

Bcd with complement, 1 pole - 10 positions single section

Color:

White single indicator background

Style Designator:

Rectangular indicating

NSN 5930-01-168-2737

Code Indicating Wheel Switch - Page 2 of 2



	••		•	_		
ı	hre	ลด	Seri	26 I I	PSIU	nator:
•		uu	CCII		COIG	mator.

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0