

View Online at <https://aerobasegroup.com/nsn/5930-01-168-3127>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.310 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.100 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.340 inches single actuator

Overall Diameter:

0.950 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Coded

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

16 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Pin

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Detent Rotational Torque Range:

+8.000/+16.000 inch-ounces single actuator

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Contact Arrangement Truth Table:

Bcd, 1 pole - 16 positions single section

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0