

View Online at <https://aerobasegroup.com/nsn/5930-01-168-3246>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

1.210 inches

**Overall Height:**

3.022 inches

**Overall Width:**

Between 0.950 inches and 0.970 inches

**Body Length:**

1.200 inches

**Body Width:**

Between 0.950 inches and 0.970 inches

**Body Height:**

2.812 inches

**Case Material:**

Metal

**Actuator Length:**

Between 1.020 inches and 1.050 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.164 inches and 0.210 inches

**Actuator Width:**

Between 0.720 inches and 0.750 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Green single actuator

**Actuator Inscription:**

Power single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Rfi shielding

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Special Features:**

Full display lens

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

12 turret and 5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0