

View Online at <https://aerobasegroup.com/nsn/5930-01-168-3310>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Actuator Length:

1.500 inches

Actuator Style:

Roller arm

Actuator Height:

1.250 inches

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.310 inches

Housing Diameter:

1.000 inches

Housing Length:

1.000 inches

Housing Bushing Length:

0.340 inches

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

1055-01-092-0596 launcher, rocket

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

144.0 inch-ounces

Switch Actuating Force:

Between 192.0 inch-ounces and 224.0 inch-ounces

Actuator Movement:

13.0 pretravel degrees and 32.0 overtravel degrees and 3.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A053a0