

View Online at <https://aerobasegroup.com/nsn/5930-01-168-3310>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Actuator Length:**

1.500 inches

**Actuator Style:**

Roller arm

**Actuator Height:**

1.250 inches

**Actuator Roller Diameter:**

0.750 inches

**Actuator Roller Width:**

0.310 inches

**Housing Diameter:**

1.000 inches

**Housing Length:**

1.000 inches

**Housing Bushing Length:**

0.340 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

1055-01-092-0596 launcher, rocket

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

144.0 inch-ounces

**Switch Actuating Force:**

Between 192.0 inch-ounces and 224.0 inch-ounces

**Actuator Movement:**

13.0 pretravel degrees and 32.0 overtravel degrees and 3.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

1 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A053a0