NSN 5930-01-168-3331

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-168-3331

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
1.120 inches
Overall Height:
2.720 inches
Overall Width:
0.870 inches
Body Width:
0.870 inches
Body Height:
2.470 inches
Case Material:
Plastic
Actuator Length:
1.000 inches
Actuator Style:
Rectangular
Actuator Height:
0.070 inches
Actuator Width:
0.760 inches
Actuator Color:
White single actuator and green single actuator
Illuminated Actuator Color:
White single actuator and green single actuator
Actuator Inscription:
Program ready single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator white lower half of actuator green
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonnilo-un Contact Arrangoment

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 750.000 milliamperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 750.000 milliamperes lamp ac

NSN 5930-01-168-3331

Push Switch - Page 2 of 2



Precious	Material	And	Location:

Contact surfaces gold

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0