

View Online at <https://aerobasegroup.com/nsn/5930-01-168-4020>

Thread Class:

2a single mounting facility

Thread Length:

0.310 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.620 inches

First Flat Length:

0.320 inches single actuator

Flat Height:

0.215 inches single actuator and 0.223 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.500 inches single actuator

Overall Diameter:

0.750 inches

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

8 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop-breakoff tab single actuator

Contact Load Current Rating:

75.0 milliamperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0