## NSN 5930-01-168-5955

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-168-5955

<b>5</b> 1 6 1
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
1.120 inches
Overall Height:
2.720 inches
Overall Width:
0.870 inches
Body Width:
0.870 inches
Body Height:
2.470 inches
Case Material:
Plastic
Actuator Length:
1.000 inches
Actuator Style:
Rectangular
Actuator Height:
0.070 inches
Actuator Width:
0.760 inches
Actuator Color:
White single actuator and green single actuator
Illuminated Actuator Color:
White single actuator and green single actuator
Actuator Inscription:
Standby ready single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator white lower half of actuator green
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonnile-un Contact Arrangement

## Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

## **Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 750.000 milliamperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 750.000 milliamperes lamp ac

## NSN 5930-01-168-5955

Push Switch - Page 2 of 2



Precious Material And Location:
Contact surfaces gold

**Terminal Type And Quantity:** 

11 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0