## NSN 5930-01-168-7503

**Hazardous Locations/environmental Protection:** 

Toggle Switch - Page 1 of 2

**Body Style:**Bushing mount

Explosion proof
Overall Length:
0.812 inches
Overall Height:
1.930 inches
Overall Width:
0.391 inches
Bushing Length:
0.469 inches



View Online at https://aerobasegroup.com/nsn/5930-01-168-7503

| Body Length:                                                                             |
|------------------------------------------------------------------------------------------|
| 0.812 inches                                                                             |
| Body Height:                                                                             |
| 0.672 inches                                                                             |
| Actuator Style:                                                                          |
| Round                                                                                    |
| Actuator Diameter:                                                                       |
| 0.240 inches                                                                             |
| Actuator Height:                                                                         |
| 0.691 inches                                                                             |
| Actuator Position-action Relationship:                                                   |
| Up position momentary and down position momentary                                        |
| Maximum Voltage Rating In Volts:                                                         |
| 250.0 ac and 30.0 dc                                                                     |
| Mounting Surface To Terminal End Distance:                                               |
| 0.708 inches                                                                             |
| Inclosure Type:                                                                          |
| Fully enclosed                                                                           |
| Mounting Method:                                                                         |
| Threaded bushing                                                                         |
| Thready Qty Per Inch (tpi):                                                              |
| 32                                                                                       |
| Thread Size:                                                                             |
| 0.469 inches                                                                             |
| Nonpile-up Contact Arrangement:                                                          |
| 1 pole, double throw, both positions maintained single switch unit                       |
| Contact Load Current Rating At Maximum Rated Voltage:                                    |
| 1.000 amperes resistive dc and 0.500 amperes inductive dc and 1.000 amperes resistive ac |
| Thread Series Designator:                                                                |
| Uns                                                                                      |
|                                                                                          |
|                                                                                          |
|                                                                                          |

## NSN 5930-01-168-7503

Toggle Switch - Page 2 of 2



| Terminal '   | Type And   | Quantity:  |
|--------------|------------|------------|
| ı errillinar | I VDE AIIU | Qualitity. |

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0