

View Online at <https://aerobasegroup.com/nsn/5930-01-168-7824>

**Hazardous Locations/environmental Protection:**

Corrosion resistant and explosion proof

**Overall Length:**

101.6 millimeters

**Overall Height:**

167.5 millimeters

**Case Material:**

Metal

**Housing Height:**

145.0 millimeters

**Housing Length:**

101.6 millimeters

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

80.0 millimeters

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

80.0 millimeters

**Maximum Voltage Rating In Volts:**

480.0 ac and 250.0 dc

**End Application:**

Ticonderoga class cg (47), cvn 68 class reactor fill auxiliary system, forrestal class cv, spruance class dd (963), supply class aoe, nimitz class cvn, oliver perry class ffg.

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

3 pole, double throw, one position momentary single switch unit

**Criticality Code Justification:**

Feat

**Actuator Movement:**

Between 15.0 pretravel degrees and 90.0 overtravel degrees and 10.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

9 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0