

View Online at <https://aerobasegroup.com/nsn/5930-01-168-7824>

Hazardous Locations/environmental Protection:

Corrosion resistant and explosion proof

Overall Length:

101.6 millimeters

Overall Height:

167.5 millimeters

Case Material:

Metal

Housing Height:

145.0 millimeters

Housing Length:

101.6 millimeters

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

80.0 millimeters

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

80.0 millimeters

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

End Application:

Ticonderoga class cg (47), cvn 68 class reactor fill auxiliary system, forrestal class cv, spruance class dd (963), supply class aoe, nimitz class cvn, oliver perry class ffg.

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

3 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Actuator Movement:

Between 15.0 pretravel degrees and 90.0 overtravel degrees and 10.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

9 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0