NSN 5930-01-169-6035

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-169-6035

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches
Body Length:
1.094 inches
Body Width:
0.406 inches
Body Height:
0.625 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.114 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Length:
0.110 inches
Actuator Style:
Rectangular
Actuator Free Position Height:
0.635 inches
Maximum Voltage Rating In Volts:
125.0 dc
End Application:
5815-01-108-5633 teleprinter
Inclosure Type:
Uninclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Actuating Force:
8.0 grams
Actuator Movement:
Between 0.047 pretravel inches and 0.050 overtravel inches and 0.010 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
100.000 milliamperes resistive dc
Precious Material And Location:
Contacts gold
Terminal Type And Quantity:

3 tab, solder lug

NSN 5930-01-169-6035

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0