## NSN 5930-01-169-7613

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-169-7613 **Body Style: Bushing mounted Body Diameter:** 0.688 inches **Bushing Length:** 1.000 inches **Body Length:** 1.000 inches **Actuator Style:** Roller plunger **Actuator Free Position Height:** 1.485 inches **Actuator Roller Diameter:** 0.375 inches **Actuator Roller Width:** 0.112 inches **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Fully enclosed Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.469 inches **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Switch Release Force:** 64.0 ounces **Switch Actuating Force:** Between 96.0 ounces and 192.0 ounces **Actuator Movement:** Between 0.040 pretravel inches and 0.125 overtravel inches and 0.020 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc **Thread Series Designator:** Uns **Terminal Type And Quantity:** 6 wire lead Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5930-01-169-7613

Sensitive Switch - Page 2 of 2



em			

No

Fiig:

A053a0