## NSN 5930-01-169-7613

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-169-7613

### Body Style:

Bushing mounted

#### **Body Diameter:**

0.688 inches

## Bushing Length:

1.000 inches

#### Body Length:

1.000 inches

#### Actuator Style:

Roller plunger

#### Actuator Free Position Height:

1.485 inches

#### Actuator Roller Diameter:

0.375 inches

#### Actuator Roller Width:

#### 0.112 inches

Maximum Voltage Rating In Volts:

28.0 dc

#### Inclosure Type:

Fully enclosed

#### Thready Qty Per Inch (tpi):

32

#### Thread Size:

0.469 inches

#### Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

64.0 ounces

#### Switch Actuating Force:

Between 96.0 ounces and 192.0 ounces

#### **Actuator Movement:**

Between 0.040 pretravel inches and 0.125 overtravel inches and 0.020 differential inches

#### Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc

#### **Thread Series Designator:**

Uns

#### **Terminal Type And Quantity:**

6 wire lead

Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5930-01-169-7613

Sensitive Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

