

View Online at <https://aerobasegroup.com/nsn/5930-01-170-0239>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

3.190 inches

Overall Width:

1.218 inches

Actuator Length:

0.720 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

Between 0.191 inches and 0.196 inches

Actuator Roller Width:

0.500 inches

Housing Height:

1.250 inches

Housing Length:

2.560 inches

Housing Width:

1.218 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.563 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.875 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

Between 48.0 ounces and 126.0 ounces

Actuator Movement:

Between 4.0 pretravel degrees and 8.0 overtravel degrees and 1.5 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 6.000 amperes lamp ac

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0