NSN 5930-01-170-0263

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-170-0263

Thread Class:

2a single mounting facility

Thread Length:

0.550 inches single mounting facility

Overall Length:

3.400 inches

Shaft Diameter:

0.750 inches single actuator

Shaft Length:

0.550 inches single actuator

Overall Diameter:

1.250 inches

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

2 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.750 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

2 each section

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

NSN 5930-01-170-0263

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

5.0 amperes resistive load dc at sea level and 5.0 amperes inductive load dc at sea level

Special Features:

Key activated with key removable at 12 o'clock

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A052b0