

View Online at <https://aerobasegroup.com/nsn/5930-01-170-0264>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.550 inches single mounting facility

**Overall Length:**

3.400 inches

**Shaft Diameter:**

0.750 inches single actuator

**Shaft Length:**

0.550 inches single actuator

**Overall Diameter:**

1.250 inches

**Individual Section Quantity:**

1

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 single section front

**Throw Quantity:**

2 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

24 single mounting facility

**Thread Size:**

0.750 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Momentary Position:**

Counterclockwise single actuator

**Rotor Through Connection Quantity:**

2 single section

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level and 2.5 amperes inductive load dc at sea level

**Special Features:**

Key activated with key removal at 12 o'clock

**Precious Material And Location:**

Contact surfaces silver and contact surfaces gold

**Precious Material:**

Silver and gold

**Style Designator:**

Snap or line

**Thread Series Designator:**

Uns single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0