

View Online at <https://aerobasegroup.com/nsn/5930-01-170-0264>

Thread Class:

2a single mounting facility

Thread Length:

0.550 inches single mounting facility

Overall Length:

3.400 inches

Shaft Diameter:

0.750 inches single actuator

Shaft Length:

0.550 inches single actuator

Overall Diameter:

1.250 inches

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section front

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.750 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Momentary Position:

Counterclockwise single actuator

Rotor Through Connection Quantity:

2 single section

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level and 2.5 amperes inductive load dc at sea level

Special Features:

Key activated with key removal at 12 o'clock

Precious Material And Location:

Contact surfaces silver and contact surfaces gold

Precious Material:

Silver and gold

Style Designator:

Snap or line

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0