## NSN 5930-01-170-0511

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-170-0511

**Thread Class:** 

2a single mounting facility

**Thread Length:** 

0.469 inches single mounting facility

**Overall Length:** 

3.094 inches

First Flat Length:

0.875 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

1.094 inches single actuator

**Overall Diameter:** 

2.000 inches

**Individual Section Quantity:** 

2

**Nonturn Device Type:** 

Slotted bushing at 12: 00 o'clock

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Method:** 

Threaded bushing single mounting facility

**Features Provided:** 

Actuator knob

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:** 

125.0 ac at sea level

**Switch Actuator Indexing Position Quantity:** 

8 single actuator

**Shaft Type:** 

Round, flatted, threaded hole single actuator

**Terminal Type:** 

Tab w/screw

**Contact Switching Action:** 

Makes before breaks, breaks before makes each section rear

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Contact Load Current Rating:** 

5.0 amperes resistive load ac at sea level

## NSN 5930-01-170-0511

Rotary Switch - Page 2 of 2



		_					
Stv	_	$\Box$	ci	an	o+	^	r.
OLV	•	UE	: 3I	ull	al	u	ı .

Tap, circular, bushing mount

**Thread Series Designator:** 

Uns single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A052b0