NSN 5930-01-170-2133

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-170-2133

Thread Class:

2b single mounting facility

Overall Length:

3.031 inches

First Flat Length:

0.750 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.000 inches single actuator

Individual Section Quantity:

4

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

1.039 inches single mounting facility

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

600.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest dc voltage rating at sea level

Style Designator:

Tap, circuit selector

NSN 5930-01-170-2133

Rotary Switch - Page 2 of 2



T	'nr	ead	Series	Desig	nator
-			-0	-00.9	

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0