

View Online at <https://aerobasegroup.com/nsn/5930-01-170-2136>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.660 inches

Overall Height:

2.430 inches

Overall Width:

0.650 inches

Bushing Length:

0.470 inches

Body Length:

0.660 inches

Body Width:

0.650 inches

Body Height:

1.280 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.680 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0