NSN 5930-01-170-2145

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-170-2145

| Body Style: |
|---|
| Bushing mount |
| Hazardous Locations/environmental Protection: |
| Corrosion resistant |
| Bushing Length: |
| 0.470 inches |
| Body Length: |
| 1.100 inches |
| Body Width: |
| 0.670 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.430 inches |
| Actuator Height: |
| 1.050 inches |
| Actuator Position-action Relationship: |
| Up position momentary and down position maintained and center position maintained |
| Actuator Position-locking Relationship: |
| Up position no locking action and down position locked in and center position locked in |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Mounting Surface To Terminal End Distance: |
| 1.100 inches |
| Inclosure Type: |
| Uninclosed |
| Mounting Method: |
| Threaded bushing |
| Features Provided: |
| Actuator seal |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.469 inches |
| Nonpile-up Contact Arrangement: |
| 4 pole, double throw, three positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |

. .

Terminal Type And Quantity:

Thread Series Designator:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

12 turret

NSN 5930-01-170-2145

Toggle Switch - Page 2 of 2



| _ | | | | | |
|----|----|----|-----|------|--|
| C. | ~~ | 14 | I i | ife: | |
| J. | 16 | | | HE. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0