

View Online at <https://aerobasegroup.com/nsn/5930-01-170-5652>

Overall Length:

45.500 inches

Ac Voltage Rating:

50.0 volts

Dc Voltage Rating:

50.0 volts

Frequency Rating:

60.0 hertz

Overall Diameter:

5.562 inches

Connector Manufacturer Code:

04034

Actuation Method:

Buoyancy

Electrical Connection Type:

Connector receptacle

Connector Identification:

34770

Internal Battery Accommodation:

Not included

Current Rating At Maximum Rated Voltage:

0.2 amperes resistive load

Voltage Rating At Maximum Rated Current:

50.0 volts

Float Quantity:

4

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

Mounting Method:

Flange

Mounting Position:

Vertical

Maximum Current Rating:

1.0 amperes resistive load

Contact Arrangement:

Spst, normally open, normally closed

Relay:

Not included

Liquid Type For Which Designed:

Hydraulic oil and lubricating oil and sea water and various fuels and water

Float Effective Travel:

Between 16.875 inches and 17.125 inches

Mounting Dimensions:

Six 0.562 in. Diameter holes equally spaced on a 4.438 in. Diameter bolt circle

Tank Insertion Length:

Between 42.938 inches and 43.062 inches

Phase:

Single

Special Features:

2nd float effective travel 11.875 in. Min, 12.125 in. Max, 3rd float effective travel 5.875 in. Min, 6.125 in. Max, 4th float effective travel 5.875 in. Min, 6.125 in. Max

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T109-d