

View Online at <https://aerobasegroup.com/nsn/5930-01-170-5687>

Inside Diameter:

0.750 inches single connection

Overall Length:

7.510 inches

Overall Height:

2.668 inches

Overall Width:

3.750 inches

Body Length:

3.880 inches

Body Height:

3.880 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Longest Horizontal Distance Between Mounting Centers:

2.380 inches

Longest Vertical Distance Between Mounting Centers:

4.630 inches

Pressure Switch Type:

Differential

Mounting Method:

Unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

400.00 pounds per square inch

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+2.50/+45.00 actuation point pounds per square inch and +2.00/+20.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Pressure Connector Type:

Swivel nut, inverted flare, threaded internal single connection

Frequency In Hertz:

400.0 single voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0