NSN 5930-01-170-5687

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-170-5687

Inside Diameter:
0.750 inches single connection
Overall Length:
7.510 inches
Overall Height:
2.668 inches
Overall Width:
3.750 inches
Body Length:
3.880 inches
Body Height:
3.880 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Longest Horizontal Distance Between Mounting Centers:
2.380 inches
Longest Vertical Distance Between Mounting Centers:
4.630 inches
Pressure Switch Type:
Differential
Mounting Method:
Unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Proof Pressure:
400.00 pounds per square inch
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
1 pole, double throw, two positions momentary
Terminal Type:
Wire lead
Contact Load Current Rating:
15.0 amperes resistive load single voltage
Contact Adjustability:
Actuation point adjustable and deactuation point adjustable
Contact Adjustment Range:
+2.50/+45.00 actuation point pounds per square inch and +2.00/+20.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point screw

NSN 5930-01-170-5687

Pressure Switch - Page 2 of 2

No Fiig: A048b0



Contact Voltage Rating In Volts: 480.0 ac at sea level single voltage Pressure Connector Type: Swivel nut, inverted flare, threaded internal single connection Frequency In Hertz: 400.0 single voltage Media For Which Designed: Gas Style Designator: Rectangular Shelf Life: N/a Unit Of Measure: - Demilitarization: