NSN 5930-01-171-5737

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-171-5737

Body Style:
Panel mounted
Overall Length:
2.450 inches
Overall Height:
1.000 inches
Body Width:
0.655 inches
Body Height:
0.905 inches
Actuator Length:
1.000 inches
Actuator Style:
Rectangular
Actuator Height:
0.250 inches
Actuator Width:
0.430 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Red single actuator and green single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.200 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes
inductive ac and 1.000 amperes lamp ac
Test Data Document:
91240 mil a 22005 anacification (includes anginearing type bullating, breehurge, etc., that reflect anacification type data in anacification

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

9 tab, solder lug

Specification Data:

81349-mil-s-22885/58 government specification

Shelf Life:

NI/o

NSN 5930-01-171-5737

Push Switch - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A053a0