

View Online at <https://aerobasegroup.com/nsn/5930-01-171-7668>

Thread Class:

2a single mounting facility

Thread Length:

0.500 inches single mounting facility

Overall Length:

1.651 inches

First Flat Length:

0.300 inches single actuator

Flat Height:

0.200 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.325 inches single actuator

Overall Diameter:

1.000 inches

Nonturn Device Radius:

0.531 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

End Application:

6625-00-445-6917 generator signal

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

11 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

11 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Contact surfaces gold and contacts silver

Precious Material:

Gold and silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0