

View Online at <https://aerobasegroup.com/nsn/5930-01-171-8483>

Hazardous Locations/environmental Protection:

Waterproof

Overall Length:

10.000 inches

Overall Height:

2.906 inches

Overall Width:

2.812 inches

Unthreaded Mounting Hole Diameter:

0.221 inches single mounting facility

Individual Section Quantity:

9

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.062 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

4 each section periphery

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

600.0 ac at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

20.0 amperes resistive load ac at sea level

Precious Material And Location:

Contact and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Square wafer, panel mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A052b0