NSN 5930-01-171-8486

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-171-8486 **Thread Class:** 2b single mounting facility **Hazardous Locations/environmental Protection:** Waterproof **Overall Length: 5.278 inches Overall Height:** 3.750 inches **Overall Width:** 3.750 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 2.297 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.297 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 3 each section periphery **Throw Quantity:** 3 each section periphery **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 30.0 dc at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 3 single actuator **Terminal Type:** Screw **Contact Switching Action:** Breaks before makes each section periphery

Switch Actuator Positioning Increment: 30.0 degrees single actuator

NSN 5930-01-171-8486

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Adjustable stop single actuator **Contact Load Current Rating:** 7.5 amperes resistive load ac at sea level **Precious Material And Location:** Contact surfaces silver **Precious Material:** Silver Style Designator: Tap, circuit selector **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A052b0