## NSN 5930-01-171-8752

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-171-8752

Hazardous Locations/environmental Protection:  Dustproof  Overall Length: 7.976 inches  Overall Height: 2.906 inches				
Overall Length: 7.976 inches Overall Height: 2.906 inches				
7.976 inches  Overall Height: 2.906 inches				
Overall Height: 2.906 inches				
2.906 inches				
Overall Width:				
2.812 inches				
Unthreaded Mounting Hole Diameter:				
0.221 inches single mounting facility				
Individual Section Quantity:				
6				
Longest Horizontal Distance Between Mounting Centers:				
2.000 inches single mounting facility				
Shortest Horizontal Distance Between Mounting Centers:				
1.000 inches single mounting facility				
Longest Vertical Distance Between Mounting Centers:				
2.188 inches single mounting facility				
Switch Contact Basic Design:				
Nonpile-up symmetrical				
Pole Quantity:				
1 each section rear				
Throw Quantity:				
7 each section rear				
Mounting Method:				
Bracket single mounting facility and unthreaded hole single mounting facility				
Features Provided:				
Actuator knob				
Contact Voltage Rating In Volts:				
600.0 ac at sea level				
Mounting Facility Pattern:				
Isosceles triangle single mounting facility				
Switch Actuator Indexing Position Quantity:				
8 single actuator				
Terminal Type:				
Tab w/screw				
Contact Switching Action:				
Breaks before makes each section rear				
Switch Actuator Positioning Increment:				
45.0 degrees single actuator				
Switch Actuator Stop Device Type:				

Fixed stop single actuator

## NSN 5930-01-171-8752

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

20.0 amperes resistive load ac at sea level

**Style Designator:** 

Tap, circuit selector

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0