NSN 5930-01-172-7249

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-172-7249

Body Style:
Hole mounted
Overall Length:
0.780 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.500 inches
Overall Height:
0.855 inches
Overall Width:
0.480 inches
Body Length:
0.780 inches
Body Width:
0.290 inches
Body Height:
0.440 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.125 inches
Actuator Style:
Rectangular
Actuator Height:
0.093 inches
Actuator Width:
0.125 inches
Actuator Free Position Height:
0.755 inches
Actuator Adapter Style:
Roller leaf
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, double make, momentary action single switch unit
Actuator Movement:
0.080 pretravel inches
Contact Load Current Rating At Maximum Rated Voltage:
10,000 amperes resistive de and 7,500 amperes industive de and 4,000 amperes lamp de and 10,000 amperes resistive as and 7,500

10.000 amperes resistive dc and 7.500 amperes inductive dc and 4.000 amperes lamp dc and 10.000 amperes resistive ac and 7.500 amperes inductive ac and 4.000 amperes lamp ac

NSN 5930-01-172-7249

Sensitive Switch - Page 2 of 2



i ei ii ii iai Tybe And Quantity.	Tε	rminal	Type	And	Quantity:	
-----------------------------------	----	--------	------	-----	-----------	--

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0