# NSN 5930-01-172-7269

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-172-7269

## **Body Style:**

Hole mounted

#### Hazardous Locations/environmental Protection:

Explosion proof

## **Overall Length:**

3.040 inches

#### **Overall Height:**

2.797 inches

#### **Overall Width:**

1.000 inches

#### Actuator Style:

Round

#### Actuator Diameter:

0.330 inches

#### **Actuator Height:**

### 1.047 inches

## Actuator Free Position Height:

1.797 inches

#### **Housing Height:**

1.750 inches

#### Housing Length:

2.460 inches

#### Housing Width:

1.000 inches

#### Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.740 inches

#### Maximum Voltage Rating In Volts:

480.0 ac

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Threaded hole

#### **Features Provided:**

Actuator seal

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

4.0 ounces

## Switch Actuating Force:

Between 6.0 ounces and 20.0 ounces

#### **Actuator Movement:**

Between 0.078 pretravel inches and 0.219 overtravel inches and 0.0005 differential inches

# NSN 5930-01-172-7269

Sensitive Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

# Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

## Fiig:

A053a0