NSN 5930-01-172-7304

Thermostatic Switch - Page 1 of 2

Silver



View Online at https://aerobasegroup.com/nsn/5930-01-172-7304

Hazardous Locations/environmental Protection:
Vibration resistant
Overall Length:
0.834 inches
Overall Height:
0.414 inches
Body Diameter:
0.660 inches
Unthreaded Mounting Hole Diameter:
0.115 inches
Distance Between Mounting Facility Centers:
0.812 inches
End Application:
Sonar set an/bqq- (v)
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Automatic reset
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
2.0 amperes resistive load second voltage
Contact Adjustability:
Actuation point not adjustable
Contact Stimulus Rating:
170.00 actuation point degrees fahrenheit and 2.00 differential point degrees fahrenheit and 4.00 differential point degrees fahrenheit
Contact Voltage Rating In Volts:
30.0 dc at sea level second voltage
Media For Which Designed:
Gas or liquid
Precious Material And Location:
Contacts silver
Precious Material:

NSN 5930-01-172-7304

Thermostatic Switch - Page 2 of 2



Style Designator:
Disc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0