NSN 5930-01-172-7537

Push Switch - Page 1 of 2



| Tusti Owiton Tuge 1 of 2 | |
|---|--|
| View Online at https://aerobasegroup.com/nsn/5930-01-172-7537 | |
| Body Style: | |
| Bushing mounted | |
| Overall Length: | |
| 1.794 inches | |
| Overall Height: | |
| 0.500 inches | |
| Overall Width: | |
| 0.500 inches | |
| Body Diameter: | |
| 0.500 inches | |
| Bushing Length: | |
| 0.266 inches | |
| Body Length: | |
| 1.250 inches | |
| Case Material: | |
| Metal | |
| Actuator Diameter: | |
| 0.303 inches | |
| Actuator Height: | |
| 0.344 inches | |
| Actuator Color: | |
| Yellow single actuator | |
| Illuminated Actuator Color: | |
| Yellow single actuator | |
| Maximum Voltage Rating In Volts: | |
| 125.0 ac and 30.0 dc | |
| End Application: | |
| 4920-01-121-6818 test station | |
| Inclosure Type: | |
| Fully enclosed | |
| Mounting Method: | |
| Threaded bushing | |
| Thread Size: | |
| 0.375 inches | |
| Nonpile-up Contact Arrangement: | |

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

0.100 amperes resistive dc and 0.100 amperes resistive ac

Precious Material And Location:

Switch terminal surfaces gold and lamp terminal surfaces silver

Unable To Decode:

Unable to decode and unable to decode

NSN 5930-01-172-7537

Push Switch - Page 2 of 2



| Thread | Series | Design | nator: |
|--------|---------------|--------|--------|
| | 0000 | -00.9. | |

Unef

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0