

View Online at <https://aerobasegroup.com/nsn/5930-01-172-8548>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Shock resistant

**Overall Length:**

2.696 inches

**Overall Height:**

0.995 inches

**Overall Width:**

0.995 inches

**Body Diameter:**

0.995 inches

**Bushing Length:**

0.330 inches

**Body Length:**

1.340 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.240 inches

**Actuator Height:**

0.826 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained and right position momentary and left position momentary

**Maximum Voltage Rating In Volts:**

28.0 dc

**Mounting Surface To Terminal End Distance:**

1.540 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 four throw, double make, normally open, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc

**Precious Material And Location:**

Contact surfaces gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0