## NSN 5930-01-172-9738

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-172-9738

| Overall Length:  |
|--|
| 0.686 inches   |
| Overall Height:  |
| 0.321 inches   |
| Body Diameter:   |
| 0.605 inches   |
| Body Height:   |
| 0.301 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.147 inches   |
| Distance Between Mounting Facility Centers:  |
| 0.437 inches   |
| Tempurature Sensing Element Type:  |
| Disc   |
| Operating Tempurature Rating:  |
| Between -55.0 degrees celsius and 260.0 degrees celsius  |
| Mounting Method:   |
| Bracket and unthreaded hole  |
| Features Provided:   |
| Hermetically sealed case   |
| Contact Action Stimulus:   |
| Increase   |
| Mounting Facility Pattern:   |
| Two position in-line   |
| Nonpile-up Contact Arrangement:  |
| 1 pole, single throw, normally closed, momentary action  |
| Terminal Type:   |
| Tab, solder lug  |
| Contact Load Current Rating:   |
| 5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage |
| Contact Adjustability:   |
| Actuation point not adjustable   |
| Contact Stimulus Rating:   |
| 190.00 actuation point degrees fahrenheit and 180.00 deactuation point degrees fahrenheit  |
| Contact Voltage Rating In Volts:   |
| 28.0 dc at sea level second voltage  |
| Frequency In Hertz:  |
| 60.0 first voltage   |
| Media For Which Designed:  |

Contacts silver

**Precious Material And Location:** 

Liquid or gas

## NSN 5930-01-172-9738

Thermostatic Switch - Page 2 of 2



| Precious Material: |
|--------------------|
| Silver             |
| Style Designator:  |
| Disc w/flange      |
| Shelf Life:        |
| N/a                |
| Unit Of Measure:   |
|                    |
| Demilitarization:  |
| No                 |

Fiig: A048b0