NSN 5930-01-172-9749

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-172-9749

Thread Class:

2b single mounting facility

Overall Length:

4.840 inches

Overall Height:

2.910 inches

Overall Width:

2.810 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.180 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

500.0 highest ac voltage rating at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Precious Material And Location:

Contact and rotor blade surfaces silver

NSN 5930-01-172-9749

Rotary Switch - Page 2 of 2

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0

