NSN 5930-01-173-1184

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-173-1184

Hazardous Locations/environmental Protection:
Shock proof
Overall Length:
3.520 inches
Overall Height:
1.740 inches
Overall Width:
2.120 inches
Unthreaded Mounting Hole Diameter:
0.189 inches single mounting facility
Individual Section Quantity:
·
1
Longest Horizontal Distance Between Mounting Centers:
1.620 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.250 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
440.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Tab w/screw
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
750.0 milliamperes resistive load ac at sea level
Style Designator:
Tap, square frame
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5930-01-173-1184Rotary Switch - Page 2 of 2



Fiig:

A052b0