

View Online at <https://aerobasegroup.com/nsn/5930-01-173-2633>

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

4.453 inches

Body Height:

4.078 inches

Unthreaded Mounting Hole Diameter:

0.297 inches

Capillary Tube Length:

72.0 inches

Bulb Length:

3.000 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

2.750 inches

Longest Vertical Distance Between Mounting Centers:

3.125 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 150.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

2 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

0.5 amperes resistive load fourth voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

-10.00/+65.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

35.00 actuation point degrees fahrenheit and 25.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

240.0 dc at sea level fourth voltage

Media For Which Designed:

Liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0