

View Online at <https://aerobasegroup.com/nsn/5930-01-173-2643>

Hazardous Locations/environmental Protection:

Humidity resistant and vibration resistant

Overall Length:

1.187 inches

Overall Height:

0.666 inches

Body Diameter:

0.640 inches

Body Height:

0.449 inches

Unthreaded Mounting Hole Diameter:

0.145 inches

Distance Between Mounting Facility Centers:

0.937 inches

End Application:

Receiving set, communications an/wlq- (v)

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Manual reset button

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable, manual reset

Contact Stimulus Rating:

140.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0