# NSN 5930-01-173-2922

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-173-2922

## **Body Style:**

Panel mount

## Hazardous Locations/environmental Protection:

Explosion proof

# **Overall Length:**

0.740 inches

## **Overall Height:**

3.060 inches

## **Overall Width:**

0.740 inches

#### **Body Length:**

0.740 inches

#### **Body Width:**

0.740 inches

#### Case Material:

Metal

# Actuator Length:

0.740 inches

# Actuator Style:

Rectangular

## Actuator Width:

0.740 inches

## Actuator Color:

Green single actuator and green single actuator

### **Illuminated Actuator Color:**

Green single actuator and green single actuator

#### **Actuator Inscription:**

Ir/pd single actuator

## Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

#### **Features Provided:**

Rfi shielding

### **Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

# Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes

inductive ac and 1.500 amperes lamp ac

## **Special Features:**

Horizontal split lens

# NSN 5930-01-173-2922

Push Switch - Page 2 of 2



Precious Material And Location: Contact surfaces gold and contacts silver Unable To Decode: Unable to decode and unable to decode Terminal Type And Quantity: 18 pin Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A053a0