NSN 5930-01-173-4947

Pressure Switch - Page 1 of 2



Tressure Owner Tage For 2
View Online at https://aerobasegroup.com/nsn/5930-01-173-4947
Inside Diameter:
0.250 inches all connections
Overall Length:
5.297 inches
Overall Height:
2.297 inches
Overall Width:
5.656 inches
Mounting Slot Width:
0.203 inches
Body Length:
3.250 inches
Body Height:
2.094 inches
Unthreaded Mounting Hole Diameter:
0.203 inches
Longest Horizontal Distance Between Mounting Centers:
4.984 inches
Longest Vertical Distance Between Mounting Centers:
0.453 inches
Pressure Switch Type:
Differential
Mounting Method:
Base and unthreaded hole and slot
Features Provided:
Electrical access port and manual reset button
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
1 pole, single throw, both positions maintained
Terminal Type:
Screw
Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+8.00/+70.00 actuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point pointer with scale

NSN 5930-01-173-4947

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts:

240.0 ac at sea level second voltage

Pressure Connector Type:

Swivel nut, flare, threaded internal all connections

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0