NSN 5930-01-173-7166

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-173-7166

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight and salt spray resistant and oiltight
Overall Length:
2.280 inches
Overall Height:
4.940 inches
Overall Width:
3.190 inches
Actuator Style:
Round
Actuator Height:
0.500 inches
Actuator Free Position Height:
0.500 inches
Housing Height:
2.600 inches
Housing Length:
4.940 inches
Housing Width:
2.280 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.218 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.812 inches
Maximum Voltage Rating In Volts:
600.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
240.0 inch-ounces
Actuator Movement

Actuator Movement

16.0 pretravel degrees and 90.0 overtravel degrees and 14.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

750.000 milliamperes resistive dc and 2.500 amperes resistive ac

NSN 5930-01-173-7166

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0