

View Online at <https://aerobasegroup.com/nsn/5930-01-174-2610>

Hazardous Locations/environmental Protection:

Dustproof and watertight

Overall Height:

2.812 inches

Overall Width:

5.188 inches

Body Length:

2.750 inches

Body Height:

2.688 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Intermediate Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

18 second threaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

216.00 pounds per square inch gage

Thread Size:

0.750 inches first threaded hole

Mounting Facility Pattern:

Obtuse triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes inductive load fifth voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+10.00/+180.00 actuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

10.00 actuation point pounds per square inch gage and 180.00 actuation point pounds per square inch gage and 14.00 differential point pounds per square inch gage and 30.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

550.0 dc at sea level eighth voltage

Pressure Connector Type:

Plain, threaded internal single connection

Special Features:

Nonmagnetic construction

Style Designator:

Rectangular

Thread Series Designator:

Npt second threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0