

View Online at <https://aerobasegroup.com/nsn/5930-01-174-2610>

**Hazardous Locations/environmental Protection:**

Dustproof and watertight

**Overall Height:**

2.812 inches

**Overall Width:**

5.188 inches

**Body Length:**

2.750 inches

**Body Height:**

2.688 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.406 inches

**Intermediate Horizontal Distance Between Mounting Centers:**

0.656 inches

**Longest Vertical Distance Between Mounting Centers:**

3.281 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Thready Qty Per Inch (tpi):**

18 second threaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

216.00 pounds per square inch gage

**Thread Size:**

0.750 inches first threaded hole

**Mounting Facility Pattern:**

Obtuse triangle

**Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained

**Terminal Type:**

Screw

**Contact Load Current Rating:**

9.6 amperes inductive load fifth voltage

**Contact Adjustability:**

Actuation point adjustable, preset

**Contact Adjustment Range:**

+10.00/+180.00 actuation point pounds per square inch gage

**Contact Adjustment Type:**

External actuation point screw

**Contact Stimulus Rating:**

10.00 actuation point pounds per square inch gage and 180.00 actuation point pounds per square inch gage and 14.00 differential point pounds per square inch gage and 30.00 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

550.0 dc at sea level eighth voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Special Features:**

Nonmagnetic construction

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt second threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0