## NSN 5930-01-174-2974

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-174-2974

Hazardous Locations/environmental Protection:				
Watertight				
Overall Length:				
3.520 inches				
Overall Height:				
1.740 inches				
Overall Width:				
2.120 inches				
Unthreaded Mounting Hole Diameter:				
0.189 inches single mounting facility				
Individual Section Quantity:				
1				
Knob Manufacturer Code:				
27192				
Knob Manufacturer Part Number:				
53-1160				
Knob Specificationial Markings:				
02 level, flt deck				
Longest Horizontal Distance Between Mounting Centers:				
1.620 inches single mounting facility				
Longest Vertical Distance Between Mounting Centers:				
1.250 inches single mounting facility				
Switch Contact Basic Design:				
Nonpile-up symmetrical				
Pole Quantity:				
2 single section rear				
Throw Quantity:				
2 single section rear				
Mounting Method:				
Unthreaded hole single mounting facility				
Features Provided:				
Actuator knob				
Contact Voltage Rating In Volts:				
440.0 highest ac voltage rating at sea level				
Mounting Facility Pattern:				
Four position rectangular single mounting facility				
Switch Actuator Indexing Position Quantity:				
2 single actuator				
Terminal Type:				
Tab w/screw				
Contact Switching Action:				

Breaks before makes single section rear

## NSN 5930-01-174-2974

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

750.0 milliamperes inductive load highest ac voltage rating at sea level

**Style Designator:** 

Square wafer, panel mount

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0