# NSN 5930-01-174-7506

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-174-7506

Hazardous Locations/environmental Protection:

Vibration resistant

**Overall Length:** 

2.516 inches

# Outside Diameter:

0.125 inches single connection

## **Body Diameter:**

1.094 inches

## **Body Length:**

1.281 inches

# **Overall Diameter:**

1.094 inches

# Pressure Switch Type:

Gage

# **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

# Mounting Method:

Input port

#### Thready Qty Per Inch (tpi):

27 single pressure connection

## **Contact Action Stimulus:**

Increase

#### **Proof Pressure:**

300.00 pounds per square inch gage

#### **Thread Size:**

0.125 inches single pressure connection

#### Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

## Sensing Element Burst Pressure:

800.00 pounds per square inch gage

#### **Terminal Type:**

Connector, receptacle

## **Contact Load Current Rating:**

5.0 amperes resistive load second voltage

#### Contact Adjustability:

Actuation point adjustable

## Contact Adjustment Range:

+15.00/+500.00 actuation point pounds per square inch gage

#### Contact Adjustment Type:

External actuation point serrated nut

#### **Contact Voltage Rating In Volts:**

30.0 dc at sea level second voltage

# NSN 5930-01-174-7506

Pressure Switch - Page 2 of 2



Pressure Connector Type:

Plain, threaded external single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

**Thread Series Designator:** 

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0